



ESP-2708-B

Infusion Pump With
Numeric Keypad



INFUSION LINE



Features

- *OLED display with improved brightness and contrast than LCD screens.*
- *Viewing the event log with time and date.*
- *Ability to operate the pump with IV sets or other marks designated.*
- *Specifications Four modes of infusion.*

Specifications

Infusion Rate Range: 0.1-1200 ml/h (or up to 200 drops/min)

Infusion Modes: ml/h drop/min volume/time patient/weight

Volume to be Infused: 1 - 9999 ml

Bolus Rate Range: 1 - 1200 ml/h

Bolus Volume: 1 - 9999 ml

Accuracy: $\pm 2\%$ on the pump only ($\pm 5\%$ with I.V set)

Built-in Infusion Rates Memory: 10 preset infusion modes memory

Built-in Multi-Languages Display: English, Spanish, French, Italian (Optional: Turkish, Russian)

KVO (Keep Vein Open): 0.1 ml/h – 3 ml/h (depends on the flow rate)

Alarm Volume: High, Medium, Low

Occlusion Sensitivity Adjustment: High, Medium, Low, Lowest 0.04 MPa -0.16 MPa / 5.8 PSI ~23.2 PSI

Alarms:

DOOR OPEN

OCCLUSION (up & down)

POWER SOURCE CHANGE

START REMINDER

INFUSION COMPLETED

I.V. SET DISENGAGED

EMPTY BAG

INITIALIZATION ERROR

DRIVE MECHANISM ERROR

AIR-IN LINE

BATTERY LOW

BATTERY DEPLETED

FW 300 Option: Connect FW300 fluid warmer to AJ5808A and share same AC power with the pump

Event Log: 400 + records of settings, running status and alarms with date and time stamps

Safety Protection: Anti-free flow protection, Automatic keypad lock, Audible & visual alarms,
Password protection

Power Supply: AC 100- 240V 50/60 Hz or DC 12V

Battery: Built-in rechargeable sealed Ni-MH, Pump will operate 4 hours min. at 25 ml/h with fully charged battery

Safety Approvals: CE 0197, IEC 60601 - 1 - 8: 2003, Type CF, IPX1

Dimensions: 105 (W) x 172 (D) x 240 (H) mm

Net Weight: 2.9 kg / 6.4 lbs



ESSE3 srl, Via Garibaldi 30
14022 Castelnuovo D.B. (AT)
Tel +39 011 99 27 706
Fax +39 011 99 27 506
e-mail esse3@chierinet.it
web: www.esse3.dreamgest.com

